

Submersible Mixer Type ABS XRW 330

The compact submersible stainless steel mixer type ABS XRW 330 is specifically designed for the major mixing functions during the homogenization of sludge and slurry.

Construction

The submersible mixer is designed as a compact, water-pressure-tight unit, including propeller and integrally cast installation bracket for attachment to a square guide tube. Maximum allowable temperature of the medium for continuous operation is 40 °C.

Motor

Premium Efficiency, IE3 equivalent, sensorless permanent-magnet motor with high overload capacity; 50 Hz; 10-pole; 400 V* using variable frequency drive (VFD) control. Protection type IP68, with stator insulation Class F. Variable frequency drive (VFD). Max. submergence 20 m.

* other voltages available

Propeller

The mixer is equipped with a special 2-blade mixed-flow propeller. With this propeller a very strong rotating turbulent flow is produced in a semi-axial flow direction. Therefore this propeller combines all properties for the homogenization of sewage sludge that belong to the intrinsic viscous substances.

Solids deflection ring

The solids deflection ring protects the mechanical seal from damage by ingress of solid or fibrous matter.

Bearings

All bearings are lubricated-for-life and maintenance-free, with a calculated lifetime of more than 100 000 h.

Shaft sealing

Sic-Sic mechanical seal at medium side.
NBR O-rings and lip seals.

Seal monitoring

System with leakage sensors (DI) in the oil**, motor and cable connection chambers.

** not in Ex version.

Temperature monitoring

Thermal sensors in the stator which open at 140 °C.

Cable


10 m sewage resistant material.
Optional lengths (m): 15, 20, 30, 40, 50.

Options

Explosion-proof version, additional seal (C-Cr) at motor side, seals in viton, vibration damper, lifting hoop.

Weight

80 kg.



System Data

Motor	PM 30/10	PM 50/10
Rated power (kW)	3.0	5.0
Motor efficiency (%)	90.7	88.9

Variable Frequency Drive (VFD)	A	B
Rated power (kW)	4.0	5.5
Rated current (A) at 400 V	9.9	12.9

Total system efficiency (%)	88.0	86.5
------------------------------------	------	------

Mixer performance

Hydraulic No.	Mixer power P_p in kW	Motor kW
3311 A	1.2	3.0
3312 A	1.5	3.0
3313 A	2.0	3.0
3311 B	2.5	5.0
3312 B	3.0	5.0
3313 B	3.5	5.0
3314 B	4.0	5.0
3315 B	4.5	5.0

Materials

Part	Material
Motor housing	1.4404 (AISI 316 L)
Sliding bracket	1.4470 (AISI 329) / polyamide (CF-8M)
Motor shaft	1.4401 (AISI 316)
Propeller	1.4571 (AISI 316 Ti)
Fasteners	1.4401 (AISI 316)
Lifting band	1.4571 (AISI 316 Ti)

[sulzer.com](https://www.sulzer.com)

Submersible Mixer Type ABS XRW 330 50Hz en 07.2025, Copyright © Sulzer Ltd 2025

This document does not provide a warranty or guarantee of any kind. Please contact us for a description of the warranties and guarantees offered with our products. Directions for use and safety will be given separately. All information herein is subject to change without notice.