

MIXPAC™

Pneumatic Dispenser TS408HM-101

2-K 50 ml 10:1 Double Syringe



Suitability <ul style="list-style-type: none"> • Force 1.6 kN (~130 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Double Syringe, 50 ml • Material Viscosity Low/Medium • Professional Use 	[mm]	50 ml 10:1	
	a	109.0	
	b	46.6	
	c	33.1	

Part Number	Article	Description	Packaging
DP250-16-300	151886	Weight 0.73 kg, Length 300 mm Reinforced Nylon Handle, Reinforced Cartridge Holder, Quick reloading	Packed individually

Product advantages	Customer benefits
Quick cartridge exchange	Effective working
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
AntiDrip	Clean application

Headquarters
 Sulzer Mixpac Ltd
 phone +41 81 772 20 00
 fax +41 81 772 20 01
 mixpac@sulzer.com
 www.sulzer.com

Denmark
 Sulzer Mixpac Denmark A/S
 phone +45 43 600 111
 mixpac@sulzer.com
 www.sulzer.com

USA, South America, Canada and Mexico
 Sulzer Mixpac USA Inc.
 phone +1 603 893 27 27
 fax +1 603 893 37 37
 mixpac@sulzer.com
 www.sulzer.com

UK and Ireland
 Sulzer Mixpac UK
 phone +44 1536 31 29 90
 fax +44 1536 31 29 85
 mixpac@sulzer.com
 www.sulzer.com

Asia Pacific
 Sulzer Mixpac China
 phone +86 21 6430 68 68
 fax +86 21 6430 66 88
 mixpac@sulzer.com
 www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS408MY-8

2-K 50 ml 1:1/2:1 or 10:1 Double Syringe



Suitability <ul style="list-style-type: none"> • Force 1.3 kN (~130 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Double Syringe, 50 ml • Material Viscosity Low/Medium • Professional Use 	[mm]	50 ml 1:1/2:1	35 ml 10:1	
	a	115.0	99.0	
	b	46.5	46.5	
	c	26.0	26.0	

Part Number	Article	Description	Packaging
DP2 50-16-100	151780	Weight 0.73 kg, Length 300 mm Reinforced Nylon Handle, Reinforced Cartridge Holder, Quick reloading	Packed individually

Product advantages	Customer benefits
Quick cartridge exchange	Effective working
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS408EM

2-K 50 ml 1:1/ 2:1/3:1 Double Syringe



Suitability <ul style="list-style-type: none"> • Force 1.6 kN, Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Double Syringe, 50 ml • Material Viscosity Low/Medium • Professional Use 	[mm]	50 ml 1:1/2:1/3:1	
	a	115.0	
	b	46.5	
	c	26.0	

Part Number	Article	Description	Packaging
DP2 50-16-200	151781	Weight 0.73 kg, Length 300 mm Reinforced Nylon Handle, Reinforced Cartridge Holder, Quick reloading	Packed individually

Product advantages	Customer benefits
Quick cartridge exchange	Effective working
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS439X-6.25kN

2-K 900 ml 2:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 6.25 kN (~625 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 900 ml • Material Viscosity High • Professional Use 	[mm]	900 ml 2:1	
	a	216.0	
	b	130.0	
	c	79.0	
	d	51.0	

Part Number	Article	Description	Packaging
DP2 900-62-100	151783	Weight 3.85 kg, Length 565 mm Reinforced Nylon Handle, Metal Cartridge Holder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
 phone +41 81 772 20 00
 fax +41 81 772 20 01
 mixpac@sulzer.com
 www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
 phone +45 43 600 111
 mixpac@sulzer.com
 www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
 phone +1 603 893 27 27
 fax +1 603 893 37 37
 mixpac@sulzer.com
 www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
 phone +44 1536 31 29 90
 fax +44 1536 31 29 85
 mixpac@sulzer.com
 www.sulzer.com

Asia Pacific

Sulzer Mixpac China
 phone +86 21 6430 68 68
 fax +86 21 6430 66 88
 mixpac@sulzer.com
 www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS459LXM

2-K 450 ml 2:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 2.7 kN (~270 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 450 ml • Material Viscosity Medium • Professional Use 	[mm]	2:1	
	a	217.0	
	b	88.0	
	c	51.0	

Part Number	Article	Description	Packaging
DP2 450-27-100	151786	Weight 2.09 kg, Length 555 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS478LXM

2-K 400 ml 10:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 2.7 kN (~270 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 400 ml • Material Viscosity Medium • Professional Use 	[mm]	10:1	
	a	184.0	
	b	92.0	
	c	69.0	
	d	25.0	

Part Number	Article	Description	Packaging
DP2 400-27-200	151787	Weight 1.86 kg, Length 497 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Quick reloading	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS483LXM

2-K 400 ml 1:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 2.7 kN (~270 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 400 ml • Material Viscosity Medium • Professional Use 	[mm]	1:1	
	a	185.0	
	b	93.0	
	c	47.0	

Part Number	Article	Description	Packaging
DP2 400-27-100	151788	Weight 1.92 kg, Length 475 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	1 unit

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS485XM

2-K 380 ml 10:1 Cartridge coaxial



Suitability <ul style="list-style-type: none"> • Force 4.0 kN (~400 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge coaxial, 380 ml • Material Viscosity High • Professional Use 	[mm]	10:1	
	a	183.0	
	b	83.0	

Part Number	Article	Description	Packaging
DP2 380-40-100	151789	Weight 2.33 kg, Length 490 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS493X

2-K 600 ml 1:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 4 kN (~400 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 600 ml • Material Viscosity High • Professional Use 	[mm]	1:1	
	a	217.0	
	b	102.0	
	c	51.0	

Part Number	Article	Description	Packaging
DP2 600-40-100	151790	Weight 2.58 kg, Length 535 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Quick reloading	1 unit

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS498XM

2-K 825 ml 10:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 4 kN (~400 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 600 ml • Material Viscosity High • Professional Use 	[mm]	10:1	
	a	217.0	
	b	106.0	
	c	79.0	

Part Number	Article	Description	Packaging
DP2 825-40-100	151791	Weight 2.73 kg, Length 580 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Quick reloading	1 unit

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS499XM

2-K 1500 ml 1:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 6.25 kN (~625 kg), Air Supply 8 bar (110 PSI) • 2-Component Cartridge, 1500 ml • Material Viscosity High • Professional Use 	[mm]	1:1	
	a	217.0	
	b	158.0	
	c	79.0	

Part Number	Article	Description	Packaging
DP2 1500-62-100	151792	Weight 3.95 kg, Length 580 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Front Handle	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters
 Sulzer Mixpac Ltd
 phone +41 81 772 20 00
 fax +41 81 772 20 01
 mixpac@sulzer.com
 www.sulzer.com

Denmark
 Sulzer Mixpac Denmark A/S
 phone +45 43 600 111
 mixpac@sulzer.com
 www.sulzer.com

**USA, South America,
Canada and Mexico**
 Sulzer Mixpac USA Inc.
 phone +1 603 893 27 27
 mixpac@sulzer.com
 fax +1 603 893 37 37
 mixpac@sulzer.com
 www.sulzer.com

UK and Ireland
 Sulzer Mixpac UK
 phone +44 1536 31 29 90
 fax +44 1536 31 29 85
 mixpac@sulzer.com
 www.sulzer.com

Asia Pacific
 Sulzer Mixpac China
 phone +86 21 6430 68 68
 fax +86 21 6430 66 88
 mixpac@sulzer.com
 www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS436LXM-410

2-K 200 ml 4:1 or 10:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 2.7 kN (~270 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 50 ml or 200 ml • Material Viscosity Medium • Professional Use 	[mm]	4:1	
	a	99.0	
	b	46.5	
	c	26.0	

Part Number	Article	Description	Packaging
DP2 200-27-100	151782	Weight 0.73 kg, Length 300 mm Reinforced Nylon Handle, Metal	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS436LXM

2-K 200 ml 1:1 or 2:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 2.7 kN (~270 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 200 ml • Material Viscosity Medium • Professional Use 	[mm]	1:1 2:1	
	a	149.0	
	b	77.0	
	c	38.0	

Part Number	Article	Description	Packaging
DP2 200-27-200	151887	Weight 1.43 kg, Length 443 mm Reinforced Nylon Handle, Integrated Rocker Arms, Standard colour Black/Grey	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters
Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark
Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

**USA, South America,
Canada and Mexico**
Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland
Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific
Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS438LXM

2-K 400 ml 4:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 4.0 kN (~400 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 400 ml ratio 4:1 • Material Viscosity Low • Professional Use 	[mm]	4:1	
	a	186.0	
	b	91.0	
	c	60.0	
	d	32.0	

Part Number	Article	Description	Packaging
DP2 400-40-300	152324	Weight 2.63 kg, Length 467 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually 10 units per master carton

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser

Headquarters

Sulzer Mixpac Ltd
 phone +41 81 772 20 00
 fax +41 81 772 20 01
 mixpac@sulzer.com
 www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
 phone +45 43 600 111
 mixpac@sulzer.com
 www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
 phone +1 603 893 27 27
 fax +1 603 893 37 37
 mixpac@sulzer.com
 www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
 phone +44 1536 31 29 90
 fax +44 1536 31 29 85
 mixpac@sulzer.com
 www.sulzer.com

Asia Pacific

Sulzer Mixpac China
 phone +86 21 6430 68 68
 fax +86 21 6430 66 88
 mixpac@sulzer.com
 www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS459XM

2-K 450 ml 2:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 4,5 kN (~450 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 450 ml • Material Viscosity Medium • Professional Use 	[mm]	2:1	
	a	217.0	
	b	88.0	
	c	51.0	

Part Number	Article	Description	Packaging
DP2 450-40-100	152516	Weight 2.69 kg, Length 555 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
 phone +41 81 772 20 00
 fax +41 81 772 20 01
 mixpac@sulzer.com
 www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
 phone +45 43 600 111
 mixpac@sulzer.com
 www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
 phone +1 603 893 27 27
 mixpac@sulzer.com
 fax +1 603 893 37 37
 mixpac@sulzer.com
 www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
 phone +44 1536 31 29 90
 fax +44 1536 31 29 85
 mixpac@sulzer.com
 www.sulzer.com

Asia Pacific

Sulzer Mixpac China
 phone +86 21 6430 68 68
 fax +86 21 6430 66 88
 mixpac@sulzer.com
 www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS483XM

2-K 400 ml 1:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 4.0 kN (~400 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 400 ml • Material Viscosity Low • Professional Use 	[mm]	1:1	
	a	185.0	
	b	93.0	
	c	47.0	

Part Number	Article	Description	Packaging
DP2 400-40-100	152309	Weight 2.60 kg, Length 475 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters
Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark
Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico
Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland
Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific
Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS483XM-21

2-K 400 ml 2:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 4.0 kN (~400 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 400 ml • Material Viscosity Low • Professional Use 	[mm]	2:1	
	a	186.0	
	b	95.0	
	c	55.0	
	d	40.0	

Part Number	Article	Description	Packaging
DP2 400-40-100	151888	Weight 2.60 kg, Length 475 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser

Headquarters

Sulzer Mixpac Ltd
 phone +41 81 772 20 00
 fax +41 81 772 20 01
 mixpac@sulzer.com
 www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
 phone +45 43 600 111
 mixpac@sulzer.com
 www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
 phone +1 603 893 27 27
 fax +1 603 893 37 37
 mixpac@sulzer.com
 www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
 phone +44 1536 31 29 90
 fax +44 1536 31 29 85
 mixpac@sulzer.com
 www.sulzer.com

Asia Pacific

Sulzer Mixpac China
 phone +86 21 6430 68 68
 fax +86 21 6430 66 88
 mixpac@sulzer.com
 www.sulzer.com

MIXPAC™

Pneumatic Dispenser TS488XM

2-K 600 ml 1:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 4.0 kN (~400 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min • 2-Component Cartridge, 600 ml • Material Viscosity Low • Professional Use 	[mm]	211	
	a	219.0	
	b	97.0	
	c	48.0	

Part Number	Article	Description	Packaging
DP2 600-40-200	152352	Weight 2.52 kg, Length 535 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com