

MIXPAC™

Pneumatic Dispenser TS483XM

2-K 400 ml 1:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 4.0 kN (~400 kg), Air Supply 8 bar (110 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 400 ml • Material Viscosity Low • Professional Use 	[mm]	1:1	
	a	185.0	
	b	93.0	
	c	47.0	

Part Number	Article	Description	Packaging
DP2 400-40-100	152309	Weight 2.60 kg, Length 475 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters
Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark
Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico
Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland
Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific
Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com