

Ultramodern corn ethanol plant in Brazil uses Sulzer's highly efficient process pumps

FS Bioenergia, located near Lucas do Rio Verde, Mato Grosso, is the first corn-only ethanol plant in Brazil. The production started in 2017 and the annual capacity is 250 million liters today. The facility utilizes the latest process technologies from ICM, an innovative company headquartered in Colwich, KS, USA that has become a world leader in biorefining technologies and processes. In addition to bioethanol, some high-value coproducts such as corn oil as well as high-protein and high-fiber dried distiller's grains are produced. The plant also generates electricity from the biomass, partly for internal use and the surplus for sale.

FS Bioenergia is recognized as the most modern and efficient corn ethanol plant in the world. The production facility is equipped with top-class pumping equipment from Sulzer and value-added, patented technologies from ICM such as Selective Milling Technology™ (SMT™), Fiber Separation Technology™ (FST™), and Base Tricanter System™ (BTS™).



Top-efficiency. Not only for pumps, but also for service provided throughout the project.

Júlio César Santana, Project Manager, FS Bioenergia



The Sulzer difference

- Recognized supplier in the biofuels market
- More than 20'000 single-stage process pumps installed in bioethanol production plants worldwide.
- Close cooperation with the customer during the whole life cycle of the equipment
- AHLSTAR and SNS pumps for demanding bioethanol applications ensure minimum power consumption, trouble-free operation, and reduced maintenance.

The challenge

Each step of ethanol production from corn involves pumps with technically demanding applications. The liquids can be complex, have high solids contents, be viscous, corrosive, hot, erosive, or explosive. The right pump materials and optimal sealing systems must be carefully selected to ensure reliable and long-lasting operation. Furthermore, all pumps must be highly efficient, both in terms of energy and water savings, so that the complete plant is operating to its full potential.

The solution

In close cooperation with the customer, we chose AHLSTAR and SNS pumps for all applications – from initial mash slurry transfer to final ethanol truck loading. In total, more than 80 single-stage pumps were installed. The AHLSTAR pumps in duplex material are handling liquids containing solids and other particles, while the SNS pumps are running on clean liquids. Most of the pumps are equipped with double mechanical seals.

Customer benefit

Sulzer has thorough experience in pumping solutions for corn-based ethanol plants worldwide. In the United States alone, more than 200 plants are in operation today, and about 70% of them are equipped with Sulzer pumps. Our successful references strengthened the confidence of the client from the very beginning of the project.

After careful commissioning and start-up, all pumps have been working perfectly. For the toughest applications, the AHLSTAR pumps with adjustable side plates provide high performances continuously. For clean liquids, the new SNS pumps simply have the highest efficiencies on the market – they exceed the benchmark efficiency index MEI 0.7.

Both the AHLSTAR and the SNS pumps have open impellers with balancing holes that optimize the shaft seal function. For pumps with double mechanical seals, it was decided after a few months' operation to switch from API piping plan 54 (external pressurized source) to API piping plan 53 (external pressurized reservoir). This change helped to further reduce the water consumption and operational costs. The versatility of the pumps and the dedicated Sulzer service technicians made this upgrade easy and fast.

During 2018, a duplicate of the existing plant will be built. This will double the production capacity of the Lucas do Rio Verde site. Extremely satisfied with the collaboration, FS Bioenergia recently ordered 65 new Sulzer pumps for this extension.

Product data

The corn ethanol plant has a total of 83 Sulzer single-stage process pumps in duplex or stainless steel 316 materials.

Pump	Single seal	Double seal
AHLSTAR	23	44
SNS	16	-

The AHLSTAR and SNS pump ranges have a wide choice of wet end sizes to cover exactly the required flows (2 to 1'230 m³/h) and heads (4 to 105 m). This allows the pumps to always run at duty points close to the best efficiency points, which means direct and maximized savings in energy costs.



AHLSTAR APP32-80 pumping unit for mash / yeast



SNS3-80 pumping unit for anhydrous ethanol

Contact

roberto.nogueira@sulzer.com

www.sulzer.com

A10256 en 6.2020, Copyright © Sulzer Ltd 2020

This study is a general product presentation. It does not provide a warranty or guarantee of any kind. Please contact us for a description of the warranties and guarantees offered with our products. Directions for use and safety will be given separately. All information herein is subject to change without notice.