

SULZER

Mixing solutions

Submersible mixer type ABS XRW



Main industries and applications

No matter the application or the size of your facility, you need a reliable, cost-effective submersible mixer that is made to work hard, day in and day out — even in the harshest conditions.

Submersible mixers type ABS XRW are robust and reliable, with an average operating life of more than a decade. They are designed to handle mixing and stirring applications in sewage treatment plants, agriculture, paper and pulp mills, and other heavy industries, including in abrasive or acidic liquids.

The XRW series can:


- Equalize sewage
- Aid biological processes (aerobic, anoxic and anaerobic)
- Be used in the selector (contact zone)
- Be used in the sludge buffer tank

They can also homogenize highly-concentrated sludge and slurries, including:

- Primary, secondary and digested sludge in storage and buffer tanks
- Lime and mineral slurries

And are certified for use in hazardous locations:


- Certified for ATEX (Ex II 2G Ex h db IIB T4 Gb)
- FM and CSA certification is available




Water and
wastewater



General
industry



Pulp, paper and
board




Designed to deliver

The versatile XRW range of mixers combine high-efficient motors with propellers that are optimized to consume the least electricity possible at every mixing speed. All our XRW mixers feature either IE3 asynchronous, or IE3-equivalent motors, which offer full speed variability and a high overload capacity, while also guaranteeing energy savings, outstanding life-cycle economy, and superior reliability.

Submersible mixers for large tanks and open waters

The XRW 210 to 900 mixers are a compact, highly efficient mixer range. The blade propellers with two or three blades are designed to achieve high thrust and therefore a high flow capacity. This optimal flow pattern ensures that our XRW mixers handle a wide range of mixing and stirring applications.


For an optimized lifecycle cost, each mixer type is equipped with the most suitable motor speed concept; asynchronous, synchronous and in combination asynchronous with gearbox.



Mixed-flow propellers handle even the thickest sludge

The dual-blade, mixed-flow propellers of the XRW 330, 480 and 750 generate a powerful, radial- and axial-rotating turbulent flow to homogenize highly concentrated sludge and slurry.

With variable speeds that can be matched to actual mixing needs, and a high overload capacity, the XRW 330 and XRW 480 are flexible, and able to adapt to seasonal shifts in wastewater volume and content. Their one-size-fits-all profiles make it easy to store spares.



Features and benefits

Premium Efficiency motors

- Guarantee the lowest possible energy consumption
- Reduce the operating temperature, extending the product life

Easy upgrade

- Suitable for use with most guiderails and lifts
- Available with a wide range of brackets and adapters

Maintenance-free bearings

- Lubricated for life
- Operating lifetime that exceeds 100'000 hours

Pre-loaded upper bearings

- Prevent spinning even in massive rag loaded applications with high turbulence
- Eliminate backlash by design, the attached spring always ensures a smooth operation
- Extend bearing life

Large rotor shafts

- Minimize deflection due to “increased” shaft diameter and stronger bearing set up

Sealed connection chambers

- Simplify maintenance by reducing the number of nuts, washers, ferrules etc.
- Safeguard the motor
- Ensure reliability because of separated chambers between motor and connection chamber

Seal systems

- Include a dependable, triple-seal system
- Feature dual oil chambers, to safeguard the motor
- Offer enhanced protection to keep the mechanical seal clog-free and extend its life

Robust planetary gearbox

- Standard on the XRW 750 and XRW 900
- Fully integrated cartridge box available also in stainless steel mixer executions

Hydraulic-optimized propeller as standard

- Ensures high-efficient mixing on all XRW mixers

Investment-cast propeller

- Ensure the best possible mixing performance
- Self-clean to reduce maintenance
- Available for XRW 210 and XRW 300

Multiple moisture sensor (DI) seal monitoring

- Secures full protection for the motor and gearbox

Abrasion-resistant, galvanically-insulated mast bracket and suspension

- Reduces the risk of electrochemical corrosion

TCS (Thermo Control System)


- Provides a warning and switches off the motor, if necessary, to prevent overheating



- ① Premium Efficiency motor
- ② Lower bearing
- ③ Upper bearing
- ④ Rotor shaft
- ⑤ Sealed connection chamber
- ⑥ Dual oil chamber
- ⑦ Mechanical seal
- ⑧ Propeller
- ⑨ Mast bracket
- ⑩ Suspension
- ⑪ TCS (Thermo Control System)

**VFD (integral part of XRW 330-650,
IP55 [NEMA 4x] or IP20 [NEMA1])**

- The permanent magnet motors are supplied with a perfectly matched VFD - just plug and play.
- Provides smart functionality such as de-ragging function, automatic and preventive propeller cleaning, product protection, moisture sensor etc.
- Adapts to changing liquid levels and/or changed process parameters, e.g., in the SBR process
- Can be used with several communication interfaces such as PROFIBUS DP, Ethernet, Modbus TCP etc.




Reject the rag with the smart XRW mixer

When fibrous material accumulates in wastewater tanks, it can impede the mixer, increase power consumption, and damage the equipment.

To prevent this, our smart XRW mixers slow, stop, and reverse direction temporarily, releasing the propeller from the rag. Once free, the propellers begin to spin again at their initial speed, in their initial direction — without downtime, and without the need for costly maintenance.

Watch video: Get rid of rags with the self-cleaning of submersible mixer type ABS XRW



Model and feature comparison

Standard feature	XRW 210-300	XRW 330, 400, 480, 650	XRW 750-900
Premium Efficiency IE3 motor	●		●
Premium Efficiency IE3-equivalent motor		●	
Variable-frequency drive (VFD), IP55 / IP21		●	
Planetary gearbox			●
Sealed connection chamber	●	●	●
Stainless steel fabricated propeller		●	●
Investment-cast propeller	●		
Moisture sensor (DI) seal monitoring	●	●	●
TCS (Thermo Control System)	●	●	●
De-rag function	●	●	●

Materials

Mixer part	CR (stainless steel)	EC (cast iron)*
Motor housing	1.4404 (AISI 316L)	EN-GJL-250 painted
Motor shaft XRW 210 - 650	1.4401 (AISI 316)	1.4021 (AISI 420)
Motor shaft / propeller shaft XRW 750 - 900	1.4021 / EN-GJS-700-3 (AISI 420 / ASTM - AISI, 100-70-03)	1.4021 / EN-GJS-700-3 (AISI 420 / ASTM - AISI, 100-70-03)
Propeller XRW 210 - 300	1.4460 (AISI 329)	1.4460 (AISI 329)
Propeller XRW 330 - 900	1.4571 (AISI 316 Ti)	1.4571 (AISI 316 Ti)
Fasteners	1.4401 (AISI 316)	1.4401 (AISI 316)

* Cast iron not available for XRW 330, XRW 400, XRW 480 and XRW 650

Operating data

	50 Hz (IE3 or equivalent**)	60 Hz (IE2* / IE3 or equivalent**)
Propeller diameter	210 to 900 mm	210 to 900 mm / 8 to 35 in.
Motor power	0.8 to 22 kW	0.9 to 25 kW / 1.2 to 33.5 hp
Motor efficiency	up to 92.3%	up to 93%
Mixing flow	up to 1.79 m ³ /s	up to 1.79 m ³ /s / up to 28'300 USgpm

* IE2 only valid for XRW 300, 60 Hz

** IE3 equivalent motor on XRW 330, XRW 400, XRW 480 and XRW 650

We're more than your partner in better wastewater management

We're your partner in better business. We take the time to understand your facility's unique situation, so we can create the best solution for you, based on the right size unit, before we even visit your site. Once there, we can adjust our mixers to meet your demands, ensuring the perfect balance of speed, power, and efficiency.

For more information about our XRW mixer series, visit sulzer.com.

The Sulzer Flow division keeps your processes flowing. Wherever fluids are treated, pumped, or mixed, we deliver highly innovative and reliable solutions for the most demanding applications.

The Flow division specializes in pumping solutions specifically engineered for the processes of our customers. We provide pumps, agitators, compressors, grinders, screens and filters developed through intensive research and development in fluid dynamics and advanced materials. We are a market leader in pumping solutions for water, oil and gas, power, chemicals and most industrial segments.

E10789 en 9.2024, Copyright © Sulzer Ltd 2024

This brochure is a general presentation. It does not provide any warranty or guarantee of any kind. Please, contact us for a description of the warranties and guarantees offered with our products. Directions for use and safety will be given separately. All information herein is subject to change without notice.

