

SULZER

Pumps and pumping systems

Submersible mixed-flow column pump type **ABS AFLX**



Main industries and applications

The submersible mixed-flow column pump type ABS AFLX equipped with a Premium Efficiency IE3 motor is designed for use where large volumes of process water or wastewater containing solid effluent must be pumped up to moderate heads.

Suitable for:

- Storm water protection, irrigation and aquaculture
- Industrial raw water and process water
- Combined sewage and surface water
- Recirculation sludge or return activated sludge (RAS)

Hazardous locations:

- Certification for ATEX (Ex II 2G Ex h db IIB T4 Gb), FM and CSA available as an option



Key customer benefits

Premium Efficiency

The AFLX pump, equipped with a Premium Efficiency IE3 motor, benefits from significant efficiency in both motor and hydraulics, resulting in substantial savings.

Great savings means a healthier environment, reducing your carbon footprint and the risk of harmful overflows. The AFLX pump makes your operation more competitive while contributing to a greener future.

Easy installation into rising main

The submersible AFLX pump can be installed according to the following, to fulfill virtually any customer requirements:

- Steel column pipe installation
- Concrete rising main installation

Automatic self-centering of the pump and column pipe by means of a conical coupling ring. No screw or bolt fixing needed.

Slimline design (optional 4-pole motor with gearbox) results in a smaller rising main design and compact pump station construction. Reduces capital investment.

Superior reliability

The AFLX pump, equipped with high standard components in hydraulic and motor, leads to outstanding reliability.



Features and benefits

Versatile range of mixed-flow impellers

- Highly efficient three-to five-blade open-type mixed-flow impellers
- Low-vibration design
- Low-NPSH design
- Trouble-free pumping of liquids containing solids in combination with screens (For detailed information please contact your local Sulzer representative)
- Applicable for delivering recirculation sludge or return activated sludge (RAS) at wastewater treatment plants

Adjustable inlet bellmouth with slotting

- Significant energy savings throughout the pump lifetime
- Ability to restore pump efficiency after wear by adjusting the inlet bellmouth
- Efficient handling of fibrous material throughout the hydraulic lifetime
- Slotted casing wear ring adapted from the ContraBlock series to ensure blockage-free operation

Slim motor design

- Opportunities for compact rising main and pumping station design
- Gearbox available from 132 kW for AFLX 1202 to 1207
- Wide range of gearbox ratios to meet the duty point with the best efficiency
- Better adaptation compared to a direct high-pole motor drive
- Higher efficiency and lower current due to the better power factor of 4-pole motors compared to high-pole motors
- Lower weight

- ① Mixed-flow propeller
- ② Double mechanical seals
- ③ Heavy-duty bearings
- ④ Stainless steel shaft
- ⑤ Premium Efficiency motor



Double mechanical seals

- Silicon carbide/silicon carbide (SiC/SiC) for maximum resistance against abrasives
- Chemical resistance in wastewater and most other industrial applications
- Seal blockage prevention that reduces operational costs

Heavy-duty stainless steel shaft

- Deflection at the mechanical seal minimized to <0.05 mm / 0.002 inches
- Increased safety against fatigue fractures
- Extended seal and bearing life

Hydraulics

AFLX 0601

AFLX 0701

AFLX 0801

AFLX 0803

AFLX 1202

AFLX 1203

AFLX 1207

Propeller type

3 blades

3 blades

3 blades (skew)

4 blades (skew)

5 blades


5 blades

5 blades**Heavy-duty bearings**

- Minimum lifetime of 100'000 hours
- Electrically insulated upper bearing as standard for PE6 and PE7, optional for PE5, which protects against stray electrical currents and avoids micro-cratering in the raceway of the inner and outer rings

Installation into rising main

- Automatic self-centering of the pump and column pipe by means of a conical coupling ring
- No screw or bolt fixing needed

Premium Efficiency IE3 motor in accordance with IEC 60034-30

Premium Efficiency submersible motors (IE3)

1 Class H (140°C / 284°F) insulation, temperature rise according to NEMA Class A up to 110 kW / 168 hp and Class B above

- Unprecedented motor reliability due to low winding temperature
- Extremely long motor lifetime

2 Service Factor up to 1.3

- A multiplier which indicates a permissible occasional power overloading, due to:
- Voltage variations, especially on long power supply lines
- Frequency deviation from the power line's frequency, (e.g. Generator-Set; very long or overloaded power lines)
- In accordance to NEMA MG1

3 Versatile cable types

- Country-specific cables with European, FM or CSA approval for use in sewage water

4 Optional shielded cable (EMC)


- For operation with frequency-controlled AC drives
- Installation according to EMC directives

5 Moisture DI probe in inspection chamber in standard execution

- Early indication of mechanical seal failure
- Additional moisture DI probe (separate for cable connection chamber and motor compartment) to provide early indication of moisture ingress, standard for PE6 and PE7 and optional for PE4 and PE5

6 Thermal protection switch in stator as standard

- Motor protection in the event of a power supply failure, e.g. low line voltage or single-phase operation
- Additional separate thermal protection switch (bimetallic, PTC or PT100) in the upper and lower bearing as an early warning of bearing malfunction, standard for PE6 and PE7 and optional for PE4 and PE5
- Vibration sensor for indication of vibration and warning when the set limit is exceeded, optional for PE4 to PE7



No. of poles		Power P2 (kW)				
		PE3	PE4	PE5	PE6	PE7
4	50 Hz	-	-	-	132-300	350-500
	60 Hz	-	-	-	150-335	400-468
6	50 Hz	9.5-22	9-37	45-90	110-200	-
	60 Hz	14-25	21-43	52-104	-	-
8	50 Hz	9-18.5	7.5-30	45-89	90-110	160-450
	60 Hz	-	17-35	43-86	104-150	-
10	50 Hz	-	-	30-55	90-132	160-350
	60 Hz	-	-	35-63	150	185-415
12	50 Hz	-	-	-	110-132	160-300
	60 Hz	-	-	-	104-150	185-290

Specifications

Materials



Pump part	Material
Motor housing / connection chamber	EN-GJL-250
Seal chamber / bearing flange	EN-GJL-250
Motor shaft	1.4021, 1.4462
Outlet diffuser	EN-GJL-250
Inlet bellmouth	EN-GJL-250, 1.4470
Impeller	EN-GJL-250, 1.4470 or 1.4469
Lifting hoop (PE3)	1.4401
Lifting hoop (PE4 and PE5)	EN-GJS-400-18, 1.4470
Lifting hoop (PE6 and PE7)	1.0060, 1.4462



Operating data

	50 Hz	60 Hz
Pipe diameters	600 to 1'200 mm	600 to 1'200 mm / 23 to 48 in.
Capacities	up to 3'100 l/s	up to 3'100 l/s / 49'000 USgpm
Heads	up to 35 m	up to 33 m / 108 ft.
Motor power	7.5 to 500 kW	17 to 468 kW / 23 to 628 hp

Performance range



The Sulzer Flow division keeps your processes flowing. Wherever fluids are treated, pumped, or mixed, we deliver highly innovative and reliable solutions for the most demanding applications.

The Flow division specializes in pumping solutions specifically engineered for the processes of our customers. We provide pumps, agitators, compressors, grinders, screens and filters developed through intensive research and development in fluid dynamics and advanced materials. We are a market leader in pumping solutions for water, oil and gas, power, chemicals and most industrial segments.

E10360 en 7.2025, Copyright © Sulzer Ltd 2025

This brochure is a general presentation. It does not provide any warranty or guarantee of any kind. Please, contact us for a description of the warranties and guarantees offered with our products. Directions for use and safety will be given separately. All information herein is subject to change without notice.

