

MIXPAC™

Pneumatic Dispenser TS459LXM

2-K 450 ml 2:1 Cartridge



Suitability <ul style="list-style-type: none"> • Force 2.7 kN (~270 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 450 ml • Material Viscosity Medium • Professional Use 	[mm]	2:1	
	a	217.0	
	b	88.0	
	c	51.0	

Part Number	Article	Description	Packaging
DP2 450-27-100	151786	Weight 2.09 kg, Length 555 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder	Packed individually

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
Long life technology	Reliable dispenser
AntiDrip	Clean application

Headquarters
Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark
Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mixpac@sulzer.com
www.sulzer.com

**USA, South America,
Canada and Mexico**
Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
mixpac@sulzer.com
fax +1 603 893 37 37
mixpac@sulzer.com
www.sulzer.com

UK and Ireland
Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific
Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com